

ELECTRIC & HYDRAULIC VALVES


G75-S | 3 Way Integral solenoid pilot control 3/4" - 2" NC




Upstream pilot control



External pilot control



Upstream pilot control



External pilot control

Technical Data

Solenoid	Supplied with 3W NO 1.2mm G75 operator
Assembly	Upstream pilot control valve is supplied with finger filter and accessories

• For technical information, refer to page 52

How to Order

G75-S	PORT	FUNCTION	MANUAL OVERRIDE	FLOW CONTROL	VOLTAGE	WIRES
3/4" BSP	50	External pilot 4	None 0	with 5	24V AC 1	two null
3/4" NPT	51	Upstream pilot 4H	Plastic 1	without ⁽¹⁾ 6	24V AC w/out Diode 1R	three ⁽²⁾ a
1" BSP	60		Handle ⁽²⁾ 2		12 V AC 3	
1" NPT	61				12 V DC 4	
1-1/2" BSP	70				24V DC 5	
1-1/2" NPT	71				24 Latch (23Ω) 6	
2" BSP	80				6 Latch (4Ω) B	
2" NPT	81				12 Latch (9Ω) C	
					16 Latch (12Ω) D	

Example : G75-S-704151

G75 1-1/2" BSP, external pilot, plastic manual override, with flow control, 24V AC, two wires.

G75-S - 70 4 1 5 1

(1) For 3/4", 1" valves only
(2) For Latch only

* To order valves manufactured according to your specific requirements, please contact our technical sales department.