


# GEM-GALIT | 3 Way pilot operated NC, NO



## Technical Data

Function	3 Way NC, NO
Ports size	1/8" BSP & NPT
Orifice size	5mm
Pressure range	1 to 10 bar
Temperature range	<b>Fluid :</b> 5°C to 50°C (no freezing) <b>Ambient :</b> -10°C to 50°C
Materials in contact with media	<b>Main Valve:</b> Reinforced Nylon <b>Solenoid Operator:</b> Stainless Steel 300 & 400 series <b>Seals:</b> NBR <b>Spring:</b> Stainless Steel AISI 300 series
Manual override	Manual override with 3 positions : • <b>AUTO</b> - for automatic operation (valve is open when solenoid is energized) • <b>MANUAL</b> - valve is kept open • <b>CLOSE</b> - valve is kept closed
Solenoid	Assembled with 3W NO GEM-OG operator, 1,6
Coil voltage	• Voltage and power consumption - see table • All Baccara coil voltages are ± 10% of nominal
Standard protection class	IP66

## How to Order

GEM-GALIT	PORT	VOLTAGE	POWER	CONNECTOR	MOUNTING BRACKET
	1/8" BSP 10	w/out coil 0	No coil 0	w/out 0	w/out 0
	1/8" NPT 11	6 1	AC8W 50Hz 1	with 1	with (2) 1
		12 2	AC8W 60Hz 2	with LED 2	
		24 3	DC10W 3	with bi-color LED 3	
		48 4	AC5.5W 50Hz 4	flying leads coil 4	
		110 5	AC5.5W 60Hz 5	with 1/2" Hub 5	
		120 6	AC2.5W 50/60Hz 6	surge protection with LED 6	
		220 7A	DC5.5W 7	connector with moulded cable 7	
		230 7	DC3.5W 8	other 9	
		240 8			
		Latch/ other (1) 9			

## Voltage & Power Consumption

V	AC (W)						DC (W)		
	50 Hz			60 Hz			10	5,5	3,5
6							•	•	•
12	•			•			•	•	•
24	•	•	•	•	•	•	•		
48	•			•			•		
110	•			•	•		•		
120	•			•					
220	•	•	•	•			•		
230	•	•	•	•	•				
240	•			•			•		

• Available options

Example : GEM-GALIT-10-3110  
GEM-GALIT pilot operated, 1/8" BSP, 24V AC8W 50Hz, with connector, without mounting bracket

GEM-GALIT 10 3 1 1 0

- (1) For specifying Latch type coil, please refer to GEM-A3P valve - How to Order table
- (2) For Latch only

\* To order valves manufactured according to your specific requirements, please contact our technical sales department